RC10 RC10		Ever	<b>æ</b>		Quality:	Main:	
	Date: _	Trea	ske		Finish:	Best Lep Tilmer	
Front Suspension:						-	
Ride Height:	7	Ball Stud Spacing:		-6	Stooning	g Bellcrank Position: Up Down	
Camber:		Dan Otud Opacing.	Q.		ocer my	g Belief drik Pusicion.	
Toe:		Ball Stud Spacing:		la .	Rall Stu	d Spacing:	
Anti-Roll Bar:		Dan Stud Spacing.	_ "		Bail Gua	d optioning.	
Arm Type:	Bumn Ste	eer Spacing:			Ball Stu	d Spacing:	
Tower Type:		Sci Opacing.	. 17	19		d Spacing:	
Wheel Hex:	Steering	Diate	5.0mr			21	
Steering Block KPI:		Tidde.	0		-		
Caster Block Insert: 0 +2.5 +5 [	╡		A		77.0		
Bulkhead Type:	=	Tile .				321) 2	
Kick-Up Angle: -2.5 0 +2.5	╡ .	<b>T</b> • _				000	
Steering Stop Spacing:	╡	The second secon	le Height:		T G		
Caster Block Spacing: Fwd Back		+3 +2	= 1			C B A	
Notes:		+1	= 1		Caster	Block Link Mount:	
Notes.		+0			Front B	ulkhead Spacing:	
Rear Suspension:							
Ride Height:	C Mount:		Axle He	eight:			
Camber:	Aluminur	m Steel	<b>○ ▼</b> 0 3	<b>▲</b> +3		420	
Anti-Roll Bar:		00000	<b>○</b> ▼1 2	+2		321	
Arm Type:	7 8888		0 1 2		Ca	amber Link Spacing:	
Tower Type:			<u> </u>		Ва	all Stud Spacing:	
Arm Spacing: Fwd Mid Back		<b>○ ▲</b> 0 3	+0		all Stud Spacing:		
Wheel Hex:							
Hub Type: Std  HRC	Aluminur	m Steel		_8			
Hub Spacing: Fwd Mid Back						69mm HD 321 — F	
Drive Shaft: CVA's Universals						9	
Notes:						200	
						ВД	
Electronics		Drivetralin		Shocks			
Radio: Servo:		Differential: Ba	ıll Diff: 🔲		Front	Rear	
EPA: Throttle: % Brake:	%	II • <del></del>	ear Diff: 🔲	Piston:			
ESC:		Diff Setting:		Thickness	s:		
ESC Settings:				Fluid:			
	Timing:	Notes:		Spring:			
Pinion: Spur:		Slipper Clutch:		Limiters:	Int: Ex	t:   Int: Ext: 9	
Battery Mount: Std Offset		Type: Stroke:					
		# of Pads:		Eyelet:	<del></del>	+9 0 +5 +9 0	
Back 1 2 3 4 5 Forward				Cup Offse			
Battery: Weight:		Notes:		Kashima	Bodies: Chr	ome Shafts: Machined Spacers:	
Notes:				Notes:			
TrackInfor	Titres		Body, W	elght#		Vehicle Comments:	
Size:	Front Tires:			Body:		Notes:	
Surface:			Front Wing:				
Traction: Front Insert:			Rear Wing:				
Moisture: Rear Tires:			Wing Angle: 0°		3° ☐ 6° ☐		
Condition:	Rear Compo	und:		Chassis Length:			
Rear Insert:			Servo Weights:				
Temperature: Notes:	Wheel (F/R): Notes:			Electronic Weights:			
			LILIOTAL Vohi	Total Vehicle Weight:			

# For more setups, visit https://www.associatedelectrics.com/teamassociated/manuals\_and\_setup\_sheets/