

SETUP SHEET



TRACK CONDITIONS

Surface: Smooth Med. Bumpy
 Size: Open Med. Tight
 Traction: High Med. Low

Track Temp/Air Temp: _____° / _____°

Note: _____

FRONT SUSPENSION

Shocks

Shock Length _____ mm

Oil _____ wt

Pison _____

Spring _____

Camber _____°

Holder Position _____ mm

Shock Length _____ mm

Front Ride Height _____ mm

REAR SUSPENSION

Shocks

Shock Length _____ mm

Oil _____ wt

Pison _____

Spring _____

Camber _____°

Holder Position _____ mm

Shock Length _____ mm

Rear Ride Height _____ mm

FRONT SUSPENSION

Upper Arm Position

Measure Under Arm Front Droop: _____ mm

Camber Link Location

Tower Mounting

Upper Arm Position

Arm Mounting

REAR SUSPENSION

Upper Arm Position

Measure Under Arm Rear Droop: _____ mm

Tower Mounting

Camber Link Location

Upright Roll Center

Arm Mounting

FRONT SUSPENSION

Toeinout

Ackermann Shim

Toe Angle: _____°

Ackermann Shim: _____ mm

REAR SUSPENSION

Rear Wheelbase Position _____ mm

Anti-Squat 1-2° 1.5-2.5°

Toe Angle 1-2° 1.5-2.5°

3-4° 3.5-4.5°

ENGINE

Gear Ratio _____ T / _____ T

Clutch Spring _____ mm Air Filter _____

Clutch Shoe _____ Plug _____

Engine _____ Manifold _____

Gasket _____ mm Muffler _____

Reducer _____ Fuel _____

DIFF OIL

Front _____ wt Other _____

Center _____ wt Other _____

Rear _____ wt Other _____

ANTI ROLL BAR

FRONT _____ /mm

REAR _____ /mm

Thickness/mm

COMMENTS

Race Time / Lap: _____

Best Lap Time: _____

Position: _____

Notes: _____

TIRE

	Front	Rear
Type	_____	_____
Inserts	_____	_____
Wheels	_____	_____

WING