

Setup Sheet for Team Associated's RC8

Rev. 2

:: Front Suspension

anti-roll bar:
 2.2 - black
 2.5 - silver
 2.8 - gold

kickup bushing
 # 2UP 1 REAR
 up down

steering rack:
 back
 mid
 front

hinge pin bushing
 # _____
 up down

camber: -2 °

caster: 16 °

toe: +1 °

ride height: 29 mm

:: Rear Suspension

anti-roll bar:
 2.2 - black
 2.5 - silver
 2.8 - gold

anti-squat bushing
 # 3
 up down

wheelbase:
 long
 medium
 short

camber: -2 °

toe: 3KHEAD

ride height: 30 mm

:: Front Shocks

spring: XRAY LITE BLUE piston: 1.6
 shock fluid: 45W length: 107MM

:: Rear Shocks

spring: XRAY LITE BLUE piston: 1.6
 shock fluid: 40W length: 126MM

:: Differentials

front fluid: 5K
 center fluid: 5K
 rear fluid: 5K

:: Wing

location: forward back
 angle: low med. high
 type: _____

:: Notes

SHOCK MEASURED FROM CENTRE OF THE HOLE TO CENTRE OF THE HOLE.

:: Engine

engine: WS7 L2G restrictor: 7MM
 muffler: AE temp: _____
 glow plug: RB
 fuel: BYRON GEN2

:: Gearing/Clutch

gearing: 16/44
 clutch shoes: 2 CARBON 1 ALLOY
 clutch spring: .9mm 1.0mm 1.1mm
 other: _____

:: Front Tires

tire: PRO-LINE HOLE SHOTS M3
 compound: STANDARD MOLDED
 insert: _____
 wheel: TL

:: Rear Tires

tire: AS PER FRONT
 compound: _____
 insert: _____
 wheel: _____

:: Race and Vehicle Comments

qualify: _____ main: _____ finish: _____ tq:
 comments: _____

EPA RESTRICTED ON THROTTLE BY 1MM MEASURED IN THE CARB. USED AS A RESTRICTOR

KING HEADZ TOP PLATE AND ARM MOUNTS USED. STD CHASSIS BRACES AND LIGHT WEIGHT BONES

:: Track Info

smooth: bumpy: blue groove:
 traction: high med. low
 soft dirt: grass: clay: wet:
 dusty: other: _____